



# Lube Control Pty Ltd

## 1:1 Air Operated Oil Pump Bar

Product Code: CK602

### PRODUCT DESCRIPTION

1:1 air operated oil pump for 205 litre drums. A faster more efficient alternative for transferring oils from 205 litre drums. Equipped with lubricator, which must be fitted, otherwise warranty will be void.



### KEY FEATURES & BENEFITS

- A faster more efficient alternative for transferring oils from 205 litre drums
- Foot valve and strainer fitted to suction pipe
- Fitted with regulator, gauge and on/off air cock
- 1/2" oil tap
- Pumps 18 litres per minute
- Ideal for filling oil jugs or bottles
- Optional drip tray to support oil jug (DIT118980011)
- Can also be optioned as wall mounted type, contact STM for details
- Equipped with lubricator — must be fitted, otherwise warranty will be void



## 1:1 Air Operated Oil Pump Bar

### TECHNICAL SPECIFICATIONS

Parameter	Value	Unit	Test Method
Model	CK602		
Drum application	205 Litre drum		
Pressure ratio	1:1		
Working pressure	20-115	psi	
Air consumption	@115psi 3.6 CFM		
Max flow rate (per min)	18	litres	
Suction tube diameter	42	mm	
Suction tube length	940	mm	
Air inlet connection	1/4" BSP Female		
Oil outlet connection	1/2" BSP Male		
— KIT BREAKDOWN —			
1:1 Air operated oil pump	DIT11701003		
Spigot	DIT1602S		
Regulator gauge	DITIAR2000		

*The information contained in this data sheet is based on data believed to be accurate at the time of publication. Lube Control Pty Ltd reserves the right to change specifications without notice. This document does not constitute a warranty, express or implied. Always refer to the product label and Safety Data Sheet before use.*