



Lube Control Pty Ltd



Product Data Sheet

Castrol Chain Spray O-R

MOTORCYCLE CHAIN LUBRICANT

Description

Castrol Chain Spray O-R is a chain lubricant for motorcycles with O-ring, X-ring and Z-ring chains. Suitable for on and offroad use.

Application

Directions for use: Shake well before use. Spray thinly and evenly on the chain. Depending on the outside temperature, wait for 10-20 minutes to allow the solvent to evaporate before using the motorcycle.

Attention: Do not spray Castrol Chain Spray O-R on tyres.

For optimum results, clean the chain with Castrol Motorcycle Parts Cleaner before applying Castrol Chain Spray O-R.

Advantages

Castrol Chain Spray O-R

- provides outstanding lubrication and protection under extreme conditions
- has excellent penetration and adhesion properties to minimize fling loss
- rapid evaporation of solvent reduces penetration time
- resists water wash-off
- protects against corrosion and aggressive environmental influences
- is low friction helping to maximise power transfer and reduce wear



Typical Characteristics

Name	Method	Units	Castrol Chain Spray O-R
Appearance	Supplier	-	w hitish dispersion
Odour	Supplier	-	characteristic
Density @ 20C	Supplier	g/ml	0.8

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Chain Spray O-R
28 Jan 2025
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890