



Lube Control Pty Ltd



Product Data Sheet

Chainsaw Oil

Chainsaw Oil

Description

Castrol Chainsaw Oil is a tacky lubricant for use on the chain, bar and sprocket of chain saws and cutter bars fitted with automatic oiling systems.

Castrol Chainsaw Oil is formulated to resist centrifugal “throw-off”, penetrate into the chain and lubricate during use, prevent wood sap from adhering to the chain and bar during operation and reduce corrosion during periods of inactivity.

Application

Castrol Chainsaw Oil is recommended for virtually all automatic saw chain lubrication systems. e.g. Dolmar, Echo, Homelite, Jonsered, Husqvarna, Poulan, Ryobi, Stihl, etc.

It is preferable NOT to mix or add **Castrol Chainsaw Oil** with any other lubricant otherwise its performance will not be maximised.

Always ensure the correct chainsaw oil (as specified by the manufacturer) is used by referring to the operators’ handbook or the Castrol Lubrication Reference Guide

Advantages

- Anti-corrosive properties limit failure and repair costs
- Increased lubricity improves cutting speed and performance
- Tackiness reduces product wastage – less lubricant is needed to cover the saw chain and cutter bar during periods of use



Typical Characteristics

Name	Method	Units	Chainsaw Oil
Appearance	Visual	-	Tacky amber oil
Density @ 15C	ASTM D4052	g/ml	0.888
Viscosity, Kinematic 40C	ASTM D445	mm²/s	135

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Chainsaw Oil
28 Oct 2022
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890