

SINGLE PEDESTAL HOSE REELS



L-AWS1015, L-AWS1215, L-OS1215, L-GS0615, L-GS1015

The Lubemate L-S Series Single Pedestal hose reel has a robust, all-steel construction, reinforced with stamped ribs to provide exceptional strength and stability. The powder-coated, corrosion-resistant finish combined with an enclosed spring design, increases longevity in the reel's lifespan. The guide arm can be adjusted in different positions to accommodate various mounting structures and its narrow footprint allows for multiple reels to take up only minimal space. The Lubemate Single Pedestal hose reel offers a reliable & cost-effective solution to your workshop.

Heavy duty steel frame
designed for robust application

Corrosion resistant
powder-coated body

Long-lasting spring
fully enclosed and lubricated



Flexible positioning of guide arm
for mounting on bench,
ceiling or wall

APPLICATIONS

Ideal for industrial and automotive field application, such as car and truck dealerships, automotive workshops, and general manufacturing.

Part Number	Fluid	Hose ID (inch)	Length	Hose Material	Pressure	Temp (°C)	Inlet	Outlet
L-AWS1015	Air/Water	3/8"	15m	NBR rubber	290 psi	80	3/8" BSPT (F)	3/8" BSPT (M)
L-AWS1215	Air/Water	1/2"	15m	NBR rubber	290 psi	80	1/2" BSPT (F)	1/2" BSPT (M)
L-OS1215	Oil	1/2"	15m	S.A.E. R1 wire braid	2320 psi	100	1/2" BSPT (F)	1/2" BSPT (M)
L-GS0615	Grease	1/4"	15m	S.A.E. R2 wire braid	5800 psi	100	1/4" BSPT (F)	1/4" BSPT (M)
L-GS1015	Grease	3/8"	15m	S.A.E. R2 wire braid	5000 psi	100	3/8" BSPT (F)	3/8" BSPT (M)