



Trico Sump Bottle with Ball Valve Drain



PRODUCT DESCRIPTION

Trico Sump Bottles with Ball Valve Drain provide reliable oil level monitoring with easy draining capability. Available in 2 oz and 5 oz capacities with centered or offset valve styles. Borosilicate Pyrex reservoir provides clear visibility of oil level and condition.

KEY FEATURES & BENEFITS

- Ball valve drain for easy and controlled oil drainage
- Available in 2 oz and 5 oz capacities
- Centered and offset valve styles available
- Borosilicate Pyrex reservoir for clear oil level visibility
- 1/2" NPT connection
- Stainless steel construction

TECHNICAL SPECIFICATIONS

Parameter	Value	Unit	Test Method
Operating Temperature	-40°F (-40°C) to 225°F (107°C)		
Reservoir	Borosilicate - Pyrex		
Gasket	Buna-N		
Materials	Stainless Steel		
31400 — Sump Bottle with Ball Valve Drain, Centered	1/2 NPT 2 oz H: 5.77" D: 3.00"		
31402 — Sump Bottle with Offset Ball Valve Drain	1/2 NPT 2 oz H: 5.77" D: 3.00"		
31405 — Sump Bottle with Ball Valve Drain, Centered	1/2 NPT 5 oz H: 6.26" D: 3.50"		
31407 — Sump Bottle with Offset Ball Valve Drain	1/2 NPT 5 oz H: 6.26" D: 3.50"		

The information contained in this data sheet is based on data considered to be accurate. No warranty is expressed or implied regarding the accuracy of this data. Product specifications and availability are subject to change without notice. Lube Control Pty Ltd accepts no responsibility for any loss or damage arising from the use of this information.