



Lube Control Pty Ltd



Product Data

Castrol GTX Professional 10W-30

Superior sludge protection to help extend engine life

Description

Castrol GTX Professional is one of the world's most trusted engine oils. It's more than just oil. It's liquid engineering that protects against problems, like sludge that your engines faces every day. S heavy traffic, poor fuel quality, harsh weather conditions and exceeding oil change intervals can all cause the build up of a tl You can't see this sludge build-up but it can damage your engine's performance and cause premature engine failure. Help extend the life of your engine with Castrol GTX Professional.

Application

Castrol GTX Professional 10W-30 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SL or earlier specification 10W-30 lubricant.

Advantages

Castrol GTX Professional 10W-30:

- Provides superior protection against engine sludge*
- Advanced protection against viscosity and thermal breakdown.
- Premium quality base oils and anti-wear additives that help extend the life of your engine.
- Helps minimize oil consumption

Castrol GTX Professional is now certified CO2 neutral according to the highest global standards. Engineered with Micro-Filt Professional's new quality standard and verified using Castrol's new Optical Particle Measurement System (OPMS) to guar: *Vs API SL limits



Typical Characteristics

Name	Method	Units	Castrol GTX Professional
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm²/s	10.4
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6600
Viscosity, Kinematic 40C	ASTM D445	mm²/s	69
Viscosity Index	ASTM D2270	None	135
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	202
Ash, Sulphated	ASTM D874	% w t	1.1

Product Performance Claims

API SL

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Professional 10W-30
21 Nov 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW