



Lube Control Pty Ltd



Product Data Sheet

Castrol Magnatec 0W-30 D

NON-STOP PROTECTION FROM EVERY START

Description

Castrol MAGNATEC has been developed to meet the unique demands of modern driving.

75% of engine wear can happen when we start the ignition. And acceleration, slowing down, and idling journeys in city driving only increase this strain. That means every congested commute, weekend getaway, and shopping trip may increase engine wear.

Castrol MAGNATEC clings like a magnet to critical engine parts and locks in place to deliver 50% better engine wear protection*. Helping to safeguard your engine's vital components - the valvetrain, timing chain, pistons, and bearings - from damage and wear.

Choose non-stop protection from every start. Choose Castrol MAGNATEC.

#ClingsLocksProtects

* Tested using an industry standard wear test, measured versus relevant industry limit.

Application

Castrol MAGNATEC 0W-30 D is suitable for use in automotive petrol and diesel vehicles where the manufacturer recommends an ACEA C2, API SP, ILSAC GF-6 SAE 0W-30 lubricant.

Castrol MAGNATEC 0W-30 D is suitable for use wherever a SAE 0W-30 meets latest Ford WSS-M2C957-A1 or Ford WSSM2C950-A specified product is called for.

Advantages

Castrol MAGNATEC clings, locks, and protects to deliver 50% better engine wear protection*.

Helping to safeguard your engine's vital components by:

- Forming a resistive barrier between metal contact points in the valvetrain
- Managing abrasive piston deposits, guarding against cylinder liner wear
- Maintaining timing chain tension and engine synchronicity by minimising chain damage and elongation
- Preserving engine bearings from corrosive wear

* Tested using an industry standard wear test, measured versus relevant industry limit.



Typical Characteristics

Name	Method	Units	Castrol Magnatec 0W-30 D
Viscosity, Kinematic 40C	ASTM D445	mm²/s	45
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	207
Density @ 15C, Relative	ASTM D4052	g/ml	0.844
Viscosity, Kinematic 100C	ASTM D445	mm²/s	9.5
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5872
Viscosity Index	ASTM D2270	None	201
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

ACEA C2
API SP
ILSAC GF-6
Meets Ford WSS-M2C957-A1
Meets Ford WSS-M2C950-A

Castrol Magnatec 0W-30 D
12 May 2026
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the SDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890