



Lube Control Pty Ltd



Product Data

Castrol Magnatec 5W-30 DX

NON-STOP PROTECTION EVEN BEFORE YOU START

Description

Castrol MAGNATEC has been developed to meet the unique demands of modern driving.

75% of engine wear can happen when we start the ignition. And acceleration, slowing down, and idling journeys in city driving only increase this strain. That means every congested commute, weekend getaway, and shopping trip may increase engine wear.

Castrol MAGNATEC clings like a magnet to critical engine parts and locks in place to deliver 50% better engine wear protection*. Helping to safeguard your engine's vital components - the valvetrain, timing chain, pistons, and bearings - from damage and wear.

Choose non-stop protection from every start. Choose Castrol MAGNATEC.

#ClingsLocksProtects

* Tested using an industry standard wear test, measured versus relevant industry limit.

Application

Castrol MAGNATEC 5W-30 DX is a full synthetic engine oil suitable for use in automotive petrol engines where the manufacturer recommends an API SQ, ILSAC GF-7 or earlier specification 5W-30 lubricant.

Castrol MAGNATEC 5W-30 DX is suitable for use for use in vehicles that require a 5W-30 lubricant that Meets Ford WSSM2C946-A/ WSS-M2C946-B1/ WSS-M2C961-A1/ WSS-M2C971-A1 specifications.

Castrol MAGNATEC 5W-30 DX is approved for use in vehicles that require a dexos1™ Gen 3 specification* 5W-30 lubricant.

*GM dexos1™ Approved-GEN 3: D330AEDA082

Advantages

Castrol MAGNATEC clings, locks, and protects to deliver 50% better engine wear protection*.

Helping to safeguard your engine's vital components by:

- Forming a resistive barrier between metal contact points in the valvetrain
- Managing abrasive piston deposits, guarding against cylinder liner wear
- Maintaining timing chain tension and engine synchronicity by minimising chain damage and elongation
- Preserving engine bearings from corrosive wear.

* Tested using an industry standard wear test, measured versus relevant industry limit.



Typical Characteristics

Name	Method	Units	Castrol MAGNATEC 5W-30 DX
Viscosity, Kinematic 40C	ASTM D445	mm²/s	63.9
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	203
Density @ 15C, Relative	ASTM D4052	g/ml	0.8480
Viscosity, Kinematic 100C	ASTM D445	mm²/s	11
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	3900
Viscosity Index	ASTM D2270	None	174
Ash, Sulphated	ASTM D874	% wt	0.92

Performance

API SQ
ILSAC GF-7
Meets Ford WSS-M2C946-A/ WSS-M2C946-B1/ WSS-M2C961-A1/M2C971-A1
GM dexos1™ Approved-Gen 3

Castrol Magnatec 5W-30 DX

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the SDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890