



Lube Control Pty Ltd



Product Data Sheet

Castrol POWER1 ULTIMATE 5W-40 4T

Outstanding Performance

Description

With so many engine oils available in the market, don't you want to know which one offers uncompromising performance?

Castrol POWER1 ULTIMATE with Full Synthetic technology is engineered for outstanding performance across 5 critical areas.

Castrol POWER1 ULTIMATE's 5-in-1 formula delivers outstanding performance and acceleration.

Application

Castrol POWER1 ULTIMATE 5W-40 4T is suitable for all makes of 4-stroke bikes, both carburetor or fuel injected where API SN (or below) and JASO MA or MA2 are recommended.

Complies with requirements of catalyst equipped engines

When choosing oil, please refer to your owner's handbook and the product specifications

Advantages

The 5-in-1 formula of full synthetic Castrol POWER1 ULTIMATE 4T 5W-40 delivers a range of benefits including:

1. Excellent acceleration*
2. Excellent protection
3. Smooth riding
4. Temperature control
5. Enduring performance

*Acceleration benefits will be subject to riding style and oil viscosity grade



Typical Characteristics

Name	Method	Units	Castrol POWER1 Ultimate 5W-40 4T
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm²/s	14.20
Viscosity, Kinematic 40C	ASTM D445	mm²/s	86.9
Viscosity Index	ASTM D2270	None	169
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	206

Product Performance Claims

API SN
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol POWER1 ULTIMATE 5W-40 4T
03 Mar 2023
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890