



Lube Control Pty Ltd



Product Data

Castrol Vecton Long Drain 15W-40 CK-4/E9

For longer useful oil life

Description

Castrol VECTON® Long Drain 15W-40 CK-4/E9 is a part synthetic heavy duty diesel engine oil that is specifically engineered to deliver longer useful oil life.

Application

It is suitable for use in high speed 4-stroke diesel engines and is compatible with diesel engines fitted with EGR. It is also compatible with the latest exhaust after treatment systems such as DPF, DOC and/or SCR.

Advantages

Castrol VECTON Long Drain with System Pro Technology™ is specifically engineered and tested for extended drains up to 80,000 kms*. Castrol Vecton Long Drain products deliver up to 45% extra performance reserve** that fights oil breakdown and also adapts to higher temperatures for longer useful oil life, giving you confidence in your maximum drain interval.

Modern trucks use new technologies resulting in different torque requirements which means higher engine temperatures and pressures. This punishes the oil, pushing it closer to breakdown, and reducing its useful life and ability to extend drain intervals. Castrol VECTON Long Drain's System Pro Technology™ has an extra performance reserve that fights oil breakdown by:

- Combating oxidation and deposits
- Neutralizing harmful acids
- Controlling oil aeration
- Also adapting to increased temperatures while resisting viscosity loss through shear.

All of this means longer useful oil life, giving you the confidence in your maximum drain interval.

* based on in-field testing. Actual oil drain depends on engine type, operating conditions, service history, OBD and fuel quality. Always use a suitable oil monitoring program. ** compared to API and ACEA industry requirements and based on tests conducted on 81% of the Castrol VECTON range by volume based on 12 months sales



Typical Characteristics

Name	Method	Units	Vecton Long Drain 15W-40 CK-4/E9
Density @ 15C	ASTM D4052	g/ml	0.873
Viscosity, Kinematic 100C	ASTM D445	mm²/s	15.9
Viscosity, Kinematic 40C	ASTM D445	mm²/s	119
Viscosity Index	ASTM D2270	None	142
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	200
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.9
Ash, Sulphated	ASTM D874	% wt	1.0

Performance

- ACEA E11, E9
- API CK-4
- JASO DH-2
- CAT ECF-3
- Approved - Cummins CES 20086
- Approved - DDC DFS 93K222
- Approved - Deutz DQC III-18 LA
- Approved - DTFR 15C100
- Approved - Meets Ford WSS-M2C171-F1
- Approved - Mack EOS-4.5
- Approved - RVI RLD-3
- Approved - Volvo VDS-4.5

Castrol Vecton Long Drain 15W-40 CK-4/E9

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the SDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890