

## LUBEMATE EL-SERIES ENCLOSED HOSE REELS



The Lubemate EL-Series Enclosed Hose Reels represent a relatively small, aesthetically neat hose containment solution for workshop applications. The reels are constructed of sturdy powder coated steel with stamped form for strength and fully enclosed spring and swivels for protection. Longevity is assured by equally robust multiple placement mounting brackets. The narrow form of the EL-Series Enclosed Hose Reels from Lubemate allow for the smallest possible wall or gantry space requirements.

**Sleek and durable enclosure**  
Designed for minimum profile


**Powder-coated steel construction**  
For longevity and corrosion protection



**High quality hose and fittings**  
Exceeds required standards

**Long lasting spring**  
Fully enclosed and lubricated

### APPLICATIONS

-  Ideal for automotive workshops where reel banks are required. Either wall mounting or from overhead gantry structures.

Part Number	L-ELAW1015	L-ELAW1210	L-EL01210	L-ELG0615
<b>Description</b>	Air/Water Hose Reel 3/8" x 15m	Air/Water Hose Reel 1/2" x 10m	Oil Hose Reel 1/2" x 10m	Grease Hose Reel 1/4" x 15m
<b>Application</b>	Air/Water	Air/Water	Oil	Grease
<b>Hose Size (ID)</b>	3/8"	1/2"	1/2"	1/4"
<b>Hose Length</b>	15m	10m	10m	15m
<b>Hose Material</b>	NBR Rubber	NBR Rubber	S.A.E 100R1 Wire Braid	S.A.E 100R2 Wire Braid
<b>Working Pressure</b>	300 psi	300 psi	2320 psi	5800 psi
<b>Max Temperature</b>	80° C	80° C	100° C	100° C
<b>Reel Inlet</b>	3/8" BSP	1/2" BSP	1/2" BSP	1/4" BSP
<b>Hose Inlet</b>	3/8" BSP	1/2" BSP	1/2" BSP	1/4" BSP