



Lube Control Pty Ltd



Product Data Sheet

Mineclean

Description

CASTROL MINECLEAN is a water based, multi-purpose, biodegradable, heavy duty detergent/degreaser with 'QUICK BREAK' properties.

Application

CASTROL MINECLEAN is designed to offer a comprehensive coverage of cleaning requirements in mining and other industries.

ENGINEERING

Degreasing
Light and Heavy Vehicle Washing
Pressure Cleaning Workshop Floors

JANITORIAL

Washroom Floors and Walls
Painted and Tiled surfaces Bench Tops
Vinyl/Plastic surfaces

Advantages

Economical to use - Up to 80:1 dilution with water. Low dilution rates can be utilised when hot water is used as a rise in temperature often assists in the cleaning action.

Tolerant to a range of water qualities i.e. hard, soft, bore & salt water.

Versatile – may be used on most surfaces.

Non-flammable – can be used underground.

Rinses freely – leaves no streaks or oily film.

Manual or equipment application – controlled foaming.

'QUICK BREAK' - Allows the splitting of oil from the wash solution via standard separator equipment.



User Advice

SURFACE	RECOMMENDED CONCENTRATION	APPLICATION
Vehicle Cleaning: All Large Mobile Equipment Trucks, cars and 4WD Chassis Tyres	1:1 to 4:1 2 0:1	Manual applications – brush and spray. Foaming equipment – Brush, sponge, swab, spray, pressure washers.
Vehicle Interiors: Carpets Vinyl	20:1 to 40:1	Use spray applicator for best results. Allow to soak for a few minutes, re-spray and rub with a cloth or brush. Wipe all cleaned surfaces with a damp cloth.
Floors & Paths: Concrete (bare/painted) Terazzo Tiles Vinyl	40:1 (well maintained floors) 5:1 (dirty, oily surfaces)	For manual or spray application apply to surface and allow to stand for up to 10 minutes, depending on condition of floor. Scrub vigorously with stiff broom. Rinse with clean water.
General Surface Cleaning: Painted areas Tiles Toilets Kitchens Canteens Showers Washrooms	10:1 to 80:1	Apply by mop, swab, spray, brush. Rinse with clean water.
High Pressure Cleaners Automatic Floor Cleaners	Recommended concentration will vary according to duty. As a guide: Cold Water: Heavy Duty = 50:1 Light Duty = 80:1 Hot Water: Heavy Duty = 50:1 Light Duty = 80:1	Refer to manufacturer's instructions for most effective results.

- Note:**
- 1. **CASTROL MINECLEAN**, although very effective in cleaning aluminum surfaces, may have a dulling effect.
 - 2. **CASTROL MINECLEAN** is more effective with hot water as the rise in temperature assists the cleaning action.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Mineclean
11 Mar 2015
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890