



Lube Control Pty Ltd



Product Data Sheet

Transmax ATF Heavy Duty

Automatic Transmission Fluid

Description

Castrol Transmax ATF Heavy Duty Automatic Transmission Fluid for Heavy Duty applications. It is approved against Allison TES 389 and Volvo 97341 Heavy Duty Automatic Transmission specifications.

Advantages

- Formulated to provide optimized seal compatibility meeting Allison TES 389 requirements.

Typical Characteristics

Name	Method	Units	Transmax ATF Heavy Duty
Density @ 15°C, Relative	ASTM D4052	g/ml	0.86
Colour	ASTM D1500	-	Red Spectrum
Appearance	Visual	-	bright and clear
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	7.2
Viscosity, Kinematic 40°C	ASTM D445	mm²/s	36
Viscosity Index	ASTM D2270	None	172
Viscosity, Brookfield @ -40°C (75W)	ASTM D2983	mPa.s (cP)	15500
Pour Point	ASTM D97	°C	- 42
Flash Point, COC	ASTM D92	°C	200

Product Performance Claims

Approved - Volvo 97341, Allison TES 389
Meets - Volvo 97340, GMDEXRON® -IIIH, Ford MERCON®

Transmax ATF Heavy Duty
22 Apr 2021
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890