

HYDRAULICS



HYDRAULICS

HYSPIN AWH-M RANGE

High quality range of shear stability, high viscosity hydraulic fluids with excellent anti-wear performance.

Suitable for use in a diverse range of hydraulic systems that are subject to wide variations in temperature.

For use in off-highway and marine applications and indoor manufacturing equipment.

FEATURES & BENEFITS

- Can be used over a wide temperature range with good shear stability
- Excellent anti-wear performance provides extended wear protection
- Reduced downtime, prolonged lubricant life.

SPECIFICATION/APPROVALS

- DIN 51502 classification – HVLP
 - ISO 6743/4 - Hydraulic Oils Type HV
 - Parker Hannifin (Denison) HF0, HF1 & HF2
 - Eaton E-FDGN-TB002-E
- Meets:
 - DIN 51524 Part 3
 - Cincinnati Lamb (Milacron) P 68-69-70
 - US Steel 126 & 127

	Hyspin AWH-M 15		Hyspin AWH-M 32	Hyspin AWH-M 46	
Pack Size	20L	205L	205L	20L	205L
Item Code	3432971	3410218	3402966	3358426	3503217
Barcode	9310084035340	9310084026546	9310084490279	9310084490422	9310084490477

	Hyspin AWH-M 68			Hyspin AWH-M 100
Pack Size	20L	205L	1000L	205L
Item Code	4103807	3402988	3378512	3900149
Barcode	9310084490620	9310084490675	9310084020971	9310084490972

